

# VTPB4 LED Vaportight Poly-Body 4'



Lumen ID	Wattage	Delivered Lumens	LPW
3500	23	3,546	154
5400	37	5,489	148
7000	47	7,091	151
11000	75	10,977	146

Delivered lumens based on 5000K CCT.

## Ordering Information

BAY		VTPB4		DAC	
Series	Family	Lumen ID	CCT	Lens Options	Voltage
1st Source LED Bay Series	Vaportight Poly-Body 4'	3500 5400 7000 11000	35K 40K 50K	DAC = Diffused Acrylic	U = Universal 120-277v 3 = 347v (Consult Factory) 4 = 480v (Consult Factory)

Dimming and Control Options	Accessories
-----------------------------	-------------

D0 = Dim to Off  
D10 = Dim to 10%  
DLV = Dim by Line Voltage  
MS = Motion Sensor  
WCM = Wireless Control

C = Cord (Specify Length)  
P = Plug (Specify NEMA)  
CHB - Chain Hanging Bail  
P/75-Pendant Mount .75 Hub  
EM = Emergency Driver

Project	
Type:	Approved By:

## APPLICATIONS

Food processing plants, breweries and bottling facilities, refrigerated storage, parking garages, roadway and pedestrian tunnels, etc.

## CONSTRUCTION

UL 5VA fiberglass housing (will not burn or melt), suitable for outdoor use, entry holes for 1/2" NPT/M20 fittings (one or both ends), 316 stainless steel retainer clips and latches, 100% impact modified acrylic polycarbonate lens (linear ribbed diffusion), stainless steel mounting hardware clip for surface mount. Stainless steel bail attachment may be provided for chain hung applications (order separately).

## SYSTEM SPECIFICATIONS

High flux linear LED modules: 85 CRI, CCT: 3500K, 4000K or 5000K. Constant current LED power supplies: power factor > 0.9, THD < 20%, universal voltage 120-277v, 347-480v available.

## DIMMING & CONTROLS

Low voltage 0-10v dimming, dim to off or dim by line voltage. Area or aisle motion sensor, wireless control system with IP protocol, A/B array switching, emergency battery back-up option.

## RATINGS & WARRANTY

Temperature rated from -40°C to 50°C (-40°F to 122°F), service life > 100,000 hours (L90), IP65, CSA listed, 5 year product warranty.

Fixture Dimensions: 51.37" x 6.40" x 4.75"

All fixtures are made in the USA.  
*"Our mission is BAA/TAA compliance."*

