

RCFM24 High Lumen Recessed Troffer

Frame Out 2x4



Project :	
Type:	Approved By:

APPLICATIONS

Production and manufacturing facilities, schools, hospitals, multi-purpose rooms, gymnasiums, industrial recessed locations.

CONSTRUCTION

.040" white pre-painted aluminum, clear or diffused acrylic lens, top access plate for quick power connection. All fixtures are 100% bench tested prior to shipping. Made in the USA.

MOUNTING

Frame out for recessed hard ceiling openings. Custom housing dimensions available. Please consult factory.

SYSTEM SPECIFICATIONS

Hi flux linear LED modules, CRI > 80, CCT: 3500K, 4000K or 5000K. Constant current LED power supplies, power factor > 0.9, THD < 20%, universal voltage 120-277v, 347-480v available.

DIMMING & CONTROLS

Low voltage 0-10v dimming, dim to off or dim by line voltage. Motion sensor, Magnum Enocean wireless protocol, A/B array switching, emergency driver battery back-up option.

RATINGS & WARRANTY

Temperature rated from -28°C to 50°C (-20°F to 122°F), service life > 100,000 hours (L90), CSA and DLC listed, BAA/TAA compliant, RoHS compliant, 5 year product warranty.





Lumen ID	CCT	Wattage	Delivered Lumens	LPW
Lens: Clear, Diffused				
12000	35K	84	12,785, 10,627	152, 127
12000	40K	84	12,901, 10,724	154, 128
12000	50K	84	13,511, 11,231	161, 134
17000	35K	118	17,542, 14,581	149, 124
17000	40K	118	17,733, 14,740	150, 125
17000	50K	118	18,538, 15,410	157, 131
19000	35K	140	18,430, 15,319	132, 109
19000	40K	140	19,457, 16,173	139, 116
19000	50K	140	18,947, 16,190	135, 116
24000	35K	170	23,889, 19,858	141, 117
24000	40K	170	24,107, 20,039	142, 118
24000	50K	170	25,247, 20,986	149, 123

Ordering Information

RSD	RCFM24					
Series	Housing	Lumen ID	CCT	Lens	Voltage	Dimming-Controls-Accessories
1st Source LED Recessed Series	Recessed Frame Out 2x4	12000 = 12,000 17000 = 17,000 19000 = 19,000 24000 = 24,000	35K 40K 50K	AC = Acrylic Clear DAC = Diffused Acrylic	U = 120-277v 3 = 347v 4 = 480v	D0 = Dim to Off D10 = Dim to 10% DLV = Dim by Line Voltage MS = Motion Sensor A/B = A/B Switching WCM = Wireless Control EM = Emergency Driver

All fixtures are made in the USA
"Our mission is BAA/TAA compliance"





TITLE: RCFM24		FILE LOCATION: \\	
3RD ANGLE PROJ:		SHEET: 1 of 1	SCALE: 1:12
UNLESS OTHERWISE NOTED:		DRAWN BY: JMG	DATE: 1/16/2019
SIZE: A	UNITS: INCHES	TOLERANCES: .X ±.06 .XX ±.03 .XXX ±.010 ∠ ±1.0°	JO: XXXX
		DWG #: RCFM24 DIMENSIONS	REV: A

1st Source Lighting
 1730 Industrial Drive, Auburn, CA 95603
 (530) 887-1110 FAX (530) 887-0807
 www.1stsourcelight.com

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF 1ST SOURCE LIGHTING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF 1ST SOURCE LIGHTING IS PROHIBITED.