

R-LED-SBF

LED Retrofit Kit for Induction Shoebox & Flood



Project	
Type:	Approved By:

CONSTRUCTION

.040 aluminum LED module tray insert with quick mount driver plates (.090 aluminum). Fastener hardware included. All kits are manufactured in the USA and 100% bench tested prior to shipping.

SYSTEM SPECIFICATIONS

LED downlight flex modules: 80+ CRI, CCT: 3500K, 4000K or 5000K. Constant current LED power supplies: power factor > 0.9, THD < 20%, universal voltage 120-277v, 347-480v available. Consult factory for dimming and controls.

RATINGS & WARRANTY

Temperature rated from -34°C to 50°C (-30°F to 122°F), service life > 100,000 hours (L90), 5 year product warranty. Consult factory for extended warranties.

Induction Model #	Induction Wattage	LED Replacement Part ID	LED Wattage	LED Lumens	LED LPW	Energy Savings
UISB or UISF 1x40	43	R-LED-SBF-2200	15	2,276	152	65%
UISB or UISF 1x70	79	R-LED-SBF-4400	31	4,354	140	61%
UISB or UISF 1x100	106	R-LED-SBF-5700	42	5,769	137	60%
UISB or UIF 1x150	161	R-LED-SBF-9100	82	9,123	111	49%
UISB or UISF 1x200	215	R-LED-SBF-10400	96	10,404	108	55%
UISB or UISF 2x150	322	R-LED-SBF-17600	160	17,658	110	50%

Ordering Information

R	LED	SBF				
Series	Light Source	Fixture Type	Part ID	CCT	Voltage	Dimming/Controls
1st Source Lighting Retrofit Kit	LED	Shoebox & Flood	2200 4400 5700 9100 10400 17600	35K 40K 50K	U = Universal 120-277v 3 = 347v 4 = 480v	Consult Factory

