

R-LED-WP

LED Retrofit Kit for Standard Induction Wall Pack



Project	
Type:	Approved By:

CONSTRUCTION

.040 aluminum LED module tray insert with quick mount driver plates (.090 aluminum). Fastener hardware included. All kits are manufactured in the USA and 100% bench tested prior to shipping.

SYSTEM SPECIFICATIONS

LED downlight flex modules: 80+ CRI, CCT: 3500K, 4000K or 5000K. Constant current LED power supplies: power factor > 0.9, THD < 20%, universal voltage 120-277v, 347-480v available. Consult factory for dimming and controls.

RATINGS & WARRANTY

Temperature rated from -34°C to 50°C (-30°F to 122°F), service life > 100,000 hours (L90). 5 year product warranty. Consult factory for extended warranties.

Induction Model #	Induction Wattage	LED Replacement Part ID	LED Wattage	LED Lumens	LED LPW	Energy Savings
UIWP 1x40	43	R-LED-WP-1400	11	1,460	133	74%
UIWP 1x70	76	R-LED-WP-2900	23	2,925	127	70%
UIWP 1x100	106	R-LED-WP-3500	28	3,485	124	73%
UIWP 1x150	145	R-LED-WP-4800	39	4,828	125	73%

Ordering Information

R	LED	WP				
Series	Light Source	Fixture Type	Part ID	CCT	Voltage	Dimming/Controls
1st Source Lighting Retrofit Kit	LED	Standard Wall Pack	1400 2900 3500 4800	35K 40K 50K	U = Universal 120-277v 3 = 347v 4 = 480v	Consult Factory

